


# AHTS "CORAL SEA FOS" (ex "PACIFIC COMMODORE")

9,000 BHP Anchor Handling Tug Supply Vessel / 80 tons bollard pull



FIVE OCEANS SALVAGE



**FIVE OCEANS SALVAGE**

54 Amalias Avenue, 105 58 Athens, Greece - Tel. (+30) 210 3258210 / Fax (+30) 210 3258219

E-mail: [contact@fiveoceansalvage.com](mailto:contact@fiveoceansalvage.com) - Website: [www.fiveoceansalvage.com](http://www.fiveoceansalvage.com)



# AHTS "CORAL SEA FOS" (ex "PACIFIC COMMODORE")

9,000 BHP Anchor Handling Tug Supply Vessel / 80 tons bollard pull

**BUILT:** Fosen Mek Verksteder A/S, 1982  
**FLAG:** Panama  
**CALL SIGN:** HO 4189  
**IMO No.** 8028474  
**CLASSIFICATION:** DNV + 1A1  
**FIFI:** 2 units x 620 m<sup>3</sup> / hour @ HSP Type 200-500 (2009)

## DIMENSIONS

Length, overall: 64.40 m  
Length B.P.: 56.40 m  
Breadth, moulded: 13.80 m  
Depth, moulded: 06.90 m  
Max Summer Draft: 05.907 m  
GRT: 1,316t  
NRT: 395t

## MACHINERY

Main engines: 2 x 4500 BHP Nohab F316V.  
Total 9,000 BHP (6711 KW)  
Rudders: 2 x Spade, capable of independent operation  
Propulsion: 2 x Ulstein CPP  
Bow Thruster: 1 x 800 BHP developing 10t of thrust.  
Generators: Auxilliary: 2 x CAT 305Kva, 440V, 60Hz, 3ph.  
Shafts: 2 x 830Kva, 440V, 60Hz, 3ph.

## PERFORMANCE / CONSUMPTION

Bollard Pull: 80t  
@10 Kts..... 16 mt/day in ballast  
In Port..... 0.7 mt/day

## TOWING AND ANCHOR HANDLING

Winch: Hydraulic Brattvaag SL250/BSL250  
Low Pressure Double Drum Waterfall Type  
Brake Capacity: 350t. 1<sup>st</sup> Layer  
Line Pull: 250t 1<sup>st</sup> Layer  
Tow Drum Cap: 1400m x 64mm wire  
Work Drum Cap: 100m x 64mm wire  
Main Tow Wire: 1400m x 64mm  
Spare Tow Wire: 1200m x 64mm  
Work Wire: 100m x 64mm  
Spare Work Wire: 600m x 76mm  
Gypsy: 2 x 27.5m x 3 inch chain  
Penant Reels Cap: 2 x 1000m x 64mm wire  
Chain Lockers: 2 lockers (117m<sup>3</sup>) Approx. 1100m of 3 inch x chain total  
Wire/Chain Stopper: Ulstein  
Towing Pins: Ulstein, Twin Pins  
Stern Roller: 3.65m x 2.5m diameter

## DECK MACHINERY

Tugger Winch: 2 x 10t  
Capstan: 2 x 6t  
Anchors/Chains: 2 x 1740kg  
Each with 540mm x 34mm chain  
K-3, 1 spare anchor  
Windlass: Brattvaag B-12-54  
Cranes: 1 x 2.Otonnes SWL & 1 x 800kg SWL

## CAPACITIES

Clear Deck Space: 38m x 11m = 418 m<sup>2</sup>  
Deck Cargo: 750t  
Fuel: 800 m<sup>3</sup>  
Potable Water: 254.9 m<sup>3</sup>

## NAVIGATION

Radar: Furuno FR-1510 MARK-3  
Radar: Tokimec BR 1510  
Gyro Compass: Sperry SR-50  
Echo Sounder: Simrad ED161  
GPS: JRC J-Nav-500/Furuno GP-90  
Communications: G.M.D.S.S.  
1 x HF SSB Sailor  
2 x VHF Sailor  
4 x VHF Portables  
2 x SART  
1 x EPIRB  
1 x Navtex

## ACCOMMODATION

8 x 1 Berths  
2 x 2 Berths  
1 x 4 Berths  
1 x 6 Berths  
Total: 22 Berths  
1 x Hospital (1 berth)  
1 x Mess-Room / Recr. Room  
1 x Galley (annex walk-in fridge and deepfreeze)

## SALVAGE EQUIPMENT

McCorkills/watercraft R5 Solas Rescue Boat with Yamaha 85HP outboard engine  
8 x 4" Submersible Pumps (460V/60Hz, 3000ltr / min)  
2 x 4" Submersible Pumps (380V/50Hz)  
2 x 3" Submersible Pumps (460V/60Hz)  
3 x 3" Air Driven Pumps (Wilden T15)  
1 x 2" Air Driven Pumps (Wilden T8)  
1 x DAN compressor MDVN 52 AP @ 5200ltr / min  
200 metres SCORPION 920C curtain type oil booms  
2 x Pneumatic Rubber Fenders of size 1.5m dia x 3.0m long  
1 x Portable Generator CATERPILLAR  
1 x Working Boat with 85HP outboard engine  
1 x Dyneema Rope 400mtrs x 64mm

## DIVING EQUIPMENT

Full set of diving equipment for 2 divers  
Underwater welding and cutting tools

## MISCELLANEOUS

Plugs for deck refrigerated containers  
Welding / Cutting Machine  
Search lights and deck flood lights

Please contact FIVE OCEANS SALVAGE prior to basing any commercial decisions on this information. FIVE OCEANS SALVAGE does not accept any liability for errors, omissions or misprints contained in the spec sheet.